



NORTON

NORTON CONSTRUCTION PRODUCTS



Concrete ▶ **C13SPM & C13SPE**

The new tough, versatile self-propelled saw specifically designed for production cutting. Balanced weight distribution and compact size makes the C13SP ideal for use as a high production green concrete saw. Standard features like a heavy-duty pointer, depth gauge, and depth lock give this saw a significant advantage over the competition. Also new as a standard feature, a five-gallon water tank to supply a mist of water aiding in dust suppression when dry cutting. The rigid steel water tank

frame is also a lifting bail positioned over the center of gravity preventing the saw from tilting when loading. The unique heavy steel one-piece pivoting blade guard design allows for cutting up to curbs and fast easy blade changes. When combined with Norton's line of premium diamond blades the C13SP is an exceptional tool for the price.

For best performance, always use genuine Norton diamond blades.

clipper

Concrete Saw ▶ C13SPM & C13SPE

FEATURES

- ▶ Premium 13 HP Honda engine with cyclone air filtration for maximum engine protection when dry cutting.
- ▶ Four V-belt drive for maximum power transmission to the blade shaft.
- ▶ Standard dual arbor blade shaft for left or right side cutting.
- ▶ Removable 5-gallon water tank with large opening for filling. Built-in fitting for external water supply.
- ▶ Recessed rear wheels allow for cutting parallel to an open trench.
- ▶ Handlebars with built-in depth gauge, automatically adjust to remain parallel to the cutting surface at all times.
- ▶ Lifting bail at the center of gravity of the saw.
- ▶ Machined flats on tight collars make easy blade removal. Pivoting blade guard for easy blade changes.

SPECIFICATIONS

MODEL:	SELF PROPELLED
C13SPM16	13HP Honda Engine Manual Start
C13SPE16	13HP Honda Engine Electric Start
C13SPE20	13HP Honda Engine Electric Start

DIMENSIONS / WEIGHTS

Length	56 inch (1422 mm)
Width	26 inch (660 mm)
Height	40 inch (1016 mm)

PERFORMANCE CHARACTERISTICS:

Max. blade diameter	16 inch
Max. depth of cut	5-1/2 inch

BLADE DIAMETER

16 inch	5-1/2 inch (127 mm)
Blade shaft diameter	1 inch (25.4 mm)
Collar diameter	4.0 inch (100 mm)
Blade shaft speed	2600 RPM
V-Belts	4

CUTTING DEPTH



HEAVY-DUTY ALL-STEEL FRONT PIVOT AXLE



4 BELT DRIVE TO FRONT AXLE



LIFTING BAIL AND WATER TANK



DESIGNED FOR GENUINE NORTON DIAMOND BLADES

Saint-Gobain Abrasives, Inc.
 2270 West Washington Street
 Stephenville, TX 76401-3798 USA

Toll free: (800) 554-8003
 Tel: (254) 968-4161
 Fax: (800) 443-1092

Sold and supported by: